

M-SERIES

| Wide Flat Panel Touchscreen

The Comark M-Series Wide Flat Panel Touchscreen can take the heat - literally. This fanless monitor can operate up to 60°C/140°F and offers a large (15.6"-24") sunlight-readable PCAP multi-touch screen. Certified to meet UL and cUL Class 1, Division 2 hazardous area standards, this panel computer is encased in an impact resistant aluminum or stainless steel housing. Plus, the entire M-Series can be further customized to meet specific industry or technical needs.

TECHNICAL SPECIFICATIONS

DISPLAY				
Display Size	15.6"	18.5"	21.5"	24"
NITs	350-nit	300-nit	250-nit	250-nit
Resolution	1920 x 1080			
Touchscreen	Projected Capacitive Multi-Touch Screen			
PROCESSOR AND STORAGE				
Operating System	Windows			
PHYSICAL				
Dimensions	15.6" 10.13" x 16.03" x 2.90" (257.3mm x 407.2mm x 73.7mm) 18.5" 11.51" x 18.51" x 2.90" (292.4mm x 470.2mm x 73.7mm) 21.5" 13.06" x 21.22" x 2.90" (331.7mm x 539.0mm x 73.7mm) 24" 14.30" x 23.45" x 2.90" (363.2mm x 595.6mm x 73.7mm)			
Weight	15.6" 15.0 lbs (6.80kg) 18.5" 19.0 lbs (8.6kg) 21.5" 19.5 lbs (8.9kg) 24" 22.0 lbs (10.0kg)			
Casing	Impact resistant Aluminum or Stainless Steel			
Temp. Operating	0-60°C (32-140°F)			
Included Accessories	Video / Touch Cables			
Power	DC/AC			
Fan/Fanless	Fanless			
Key Variants	AC, DC, Stainless Bezel			
Ports, Slots & Peripherals	USB Touch Input			
DOCUMENTATION				
Certification	FCC/CE/UL 508/C1D2			
Warranty	2 years			

Looking for different specifications to meet your application needs? We are specialists in custom engineered solutions. [Contact us to learn more.](#)

